



IMPACT RESISTANCE: 550 J

Rif. UNI EN 22768/1

Classe di tolleranza	Desig.	Denominazione.	Scostamenti limite per dimensioni lineari *							
			0,5°	>3	>6	>30	>120	>400	>1000	>2000
			±3	±6	±30	±120	±400	±1000	±2000	±4000
f		fine	±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	
m		media	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2
c		grossolana	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4
v		molto grossolana		±0.5	±1	±1.5	±2.5	±4	±6	±8

* Esclusi smussi e raccordi per eliminazione di spigoli.
* Per dimens. < di 0.5 mm, lo scostamento si indica dopo la dimens.

Rev. n°. 00	Data 25/01/16	Modifica: Prima emissione	Firma Fabio M.	
<p>ESTRUSIONE MATERIE PLASTICHE Via Europa 2, Fratte (PADOVA) Italy www.mpmpvc.com E-mail: info@mpmpvc.com Tel +39.049.9301773 Fax +39.049.9300427</p>		Materiale PVC	Q.tà _____	1° Controllo _____
		Scala 1:1	Denominazione HAND RAIL ESP	Nr. Disegno _____