



Rif. UNI EN 22768/1

Classe di tolleranza	Desig.	Denominazione.	Scostamenti limite per dimensioni lineari *							
			0,5° ±3	>3 ±6	>6 ±30	>30 ±120	>120 ±400	>400 ±1000	>1000 ±2000	>2000 ±4000
f	fine		±0.05	±0.05	±0.1	±0.15	±0.2	±0.3	±0.5	
m	media		±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2
o	c	grossolana	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	±4
v		molto grossolana		±0.5	±1	±1.5	±2.5	±4	±6	±8

\* Esclusi smussi e raccordi per eliminazione di spigoli.

\* Per dimens. < 0.5 mm, lo scostamento si indica dopo la dimens.

Rev. n°. 00    Data 23/11/15    Modifica: Prima emissione

Firma Fabio M.



Materiale PVC

Q.tà \_\_\_\_\_

1° Controllo \_\_\_\_\_

Scala

Denominazione

Nr. Disegno \_\_\_\_\_

2° Controllo \_\_\_\_\_



RPS 600

Via Europa 2, Fratte (PADOVA) Italy  
www.mpmpvc.com E-mail: info@mpmpvc.com  
Tel +39.049.9301773 Fax +39.049.9300427